

### MPP-VDSL

#### Modular plug protector VDSL

The Modular Plug Protector provides protection for twisted pair fibre to node telecommunication services, suitable for telephones, FAX, dial-up, modems connected on VDSL2


#### NBN compatible

The MPP-VDSL is suitable for NBN fibre node to premises copper VDSL2 connection





Image for illustrative purposes only

#### Wiring



#### Dimensions



## Product Datasheet

## Electrical Specifications

Connection type		Series
Number of lines		1 pair
Modes of protection		Transverse & Common
Maximum continuous voltage (DC)	$U_c$	230V
Maximum continuous voltage (AC)	$U_c$	162V
Maximum discharge current (8/20 $\mu$ s)	$I_{max}$	5kA
Maximum common mode discharge current (8/20 $\mu$ s)		10kA
Maximum discharge current (10/350 $\mu$ s)	$I_{imp}$	1.25kA
Maximum common mode discharge current (10/350 $\mu$ s)	$I_{imp}$	2.5kA
Impulse durability C2 10x8/20 $\mu$ s		1.5kA
Impulse durability D1 2x10/350 $\mu$ s		0.5kA
AC durability 5x1s		1A rms
Overstressed fault mode		Mode 3
Response time	$t_A$	<25ns
Line resistance		0.1 $\Omega$
3 dB Frequency @ 150 $\Omega$		80MHz
Earthing		>400V isolation

## Electrical (L-L) Specifications

Voltage protection level @ 1 kV/ $\mu$ s	$U_p$	950V
Capacitance	- -	8pF

## Electrical (L-PE) Specifications

Voltage protection level @ 1 kV/ $\mu$ s	$U_p$	770V
Voltage protection level @ 100 V/ s		440V
Capacitance	- -	8pF

## Mechanical Specifications

Minimum operating temperature		-40°C
Maximum operating temperature		70°C
Minimum operating humidity		5%
Maximum operating humidity		95%
Mounting method		Free standing
Environmental rating		IP20
Enclosure material		Aluminium
Enclosure finish		Black powdercoat
Terminal type		RJ45
Length		80mm
Width		27mm
Height		28mm

## Standard Specifications

IEC 61643-21	SPD connected to telecommunications and signalling networks - Cat C2, D1
AS 1768	Signalling/Telecommunications surge protection
AS/NZS 4117	Surge Protective Devices for Telecommunications Applications

## Shipping Specifications

Weight		200g
Customs tariff		85363000, 85363010

## Other Specifications

Product Code		MPP-VDSL
--------------	---	----------