

### IFD2-6-10-275

#### Two Phase DIN Mount Surge Filters

The Novaris IFD2 range of surge filters is designed for protecting floating AC or DC power supplies. Applications include DC power supplies, balanced circuits for rail applications and single phase IT systems.

#### Multistage Protection

The IFD2 uses 3 stages of protection to provide a low let through voltage. The first stage comprises a delta configuration of metal oxide varistors to provide clamping between both lines and between each line and earth. The second stage is a low pass filter providing instantaneous protection against high frequency impulses. The third stage is a line to line metal oxide varistor to provide an extra level of protection against primary and load side surges.

#### No Earth Leakage

The IFD2 configuration results in zero earth leakage under normal operating conditions. The earth reference for the product is isolated using a spark gap. This means even in the event of a short circuit failure within the device, no current will pass to earth.

#### Safe Metal Enclosure

Novaris power protection products are housed in safe, all metal enclosures. In the event of a prolonged overvoltage they will not catch fire or explode.


#### Installation Independent Performance

Series surge protectors such as the SSP and IFD range house the shunt (parallel) connection of the protection components internally within the device. This reduces the connection impedance to a minimum to guarantee optimal performance in all installations.




Image for illustrative purposes only

### Wiring



### Dimensions



## Product Datasheet

## Electrical Specifications

Connection type		Series
Modes of protection		(+)-(-), (+)-PE, (-)-PE
Number of ports		2
Number of phases		2
Location		Indoor
Nominal voltage	$U_0$	230VAC
Maximum backup fuse		6A

## Electrical (L-L) Specifications

Maximum load current	$I_L$	6A
Maximum continuous voltage AC	$U_c$	275VAC
Maximum continuous voltage DC	$U_c$	350VDC
Maximum discharge current (8/20 $\mu$ s)	$I_{max}$	10kA
Nominal discharge current (8/20 $\mu$ s)	$I_n$	6kA
Voltage protection level (3kA 8/20 $\mu$ s)	$U_p$	<700V

## Electrical (L-PE) Specifications

Maximum discharge current (8/20 $\mu$ s)	$I_{max}$	40kA
Nominal discharge current (8/20 $\mu$ s)	$I_n$	40kA
Voltage protection level @ 1 kV/ $\mu$ s	$U_p$	<700V
Response time	$t_A$	<25ns

## Indication Specifications

Display		LED power and thermal failure
---------	--	-------------------------------

## Mechanical Specifications

Minimum operating temperature		-40°C
Maximum operating temperature		70°C
Minimum operating humidity		5%
Maximum operating humidity		95%
Mounting method		TS35 DIN Rail
Environmental rating		IP20
Enclosure material		Aluminium
Enclosure finish		Black powdercoat
Terminal capacity - power		2.5mm <sup>2</sup>
Terminal screw torque - power		0.5Nm
Length		115mm
Width		18mm
Height		69mm

## Standard Specifications

IEC 61643-11	SPD connected to low-voltage power systems - Type 1, 2
AS 1768	AC power system SPD - Cat C, B, A
UL 1449	Low voltage SPD - Type 2, 3
IEEE 62.41.2	Low voltage SPD - Cat B

## Shipping Specifications

Weight		150g
Customs tariff		85363000, 85363010

## Other Specifications

Product Code		IFD2-6-10-275
--------------	--	---------------